


LED-Light kit ECO PLANO II


Ultra-flat yet bright as day: the ready-to-install luminair complements the ECO PLANO II and immerses your room in a cosy, warm white light.

- Opal glass lamp with LED panel, 12 Watt
- Dimmable via the remote control of ECO PLANO II.
- Quick and easy installation, subsequent connection possibe.
- Overall height only 35 mm.
- Available in all housing finishes.











15

The luminaire contains built-in LED lamps. Energy class D (Spectrum A to G). The lamps cannot be changed in the luminaire. Replacement LED modules available.

Product	Code No.	Housing Finish
Light kit EP-LED BN	2761	Brushed chrome
Light kit EP-LED WE	2762	White
Light kit EP-LED BG	2763	Basalt grey
Light kit EP-LED BZ	2764	Antique bronze
Light kit EP-LED LG	2765	Light grey

- Very low profile for installation in low-ceilinged rooms.
- Available in two sizes: for small rooms up to 15 m² and for medium rooms up to 22 m².

Ø 190

Ø 160

Ø 1120/1320

- Forward/reverse (summer/winter) by remote control.
- 6 speeds by remote control, incl. light on/off/dimming and sleep timer.
- Balanced motor and blades.
- 4 blades included: 2, 3 or 4 installable.

Options:

- Dimmable light kits type EP-LED adaptable
- Hotel wall control FB-FNK ECO A #86200 (p. 133).

ECO PLANO II 112

LCO I LA	10 11 1	-			
Product	Code No.	Code No.	Ø cm	Housing Finish	Blade Finish
112 BN-SI	311280	311280W	112	Brushed chrome	Silver
112 WE-WE	311283	311283W	112	White	White
112 BG-BG	311284	311284W	112	Basalt grey	Basalt grey
112 BZ-NB	311282	311282W	112	Antique bronze	Walnut
112 LG-LG	311285	311285W	112	Light grey	Light grey

ECO PLANO II 132

Product	Code No.	Code No.	Ø cm	Housing Finish	Blade Finish
132 BN-SI	313280	313280W	132	Brushed chrome	Silver
132 WE-WE	313283	313283W	132	White	White
132 BG-BG	313284	313284W	132	Basalt grey	Basalt grey
132 BZ-NB	313282	313282W	132	Antique bronze	Walnut
132 LG-LG	313285	313285W	132	Light grey	Light grey

Further technical data on pages 122 and 126

112

1.0 - 13 1.1 - 28

100-240/50-60

112/44 132/52

30 - 208 30 - 207

6.4

5.9

No. of blades

Power motor (W)

Voltage (V/Hz)

Size Ø (cm/")

Rev. (RPM)

Weight (kg)

No. of speeds (with R/C)

separation 68 - 94 mm

Installation: 2 screws Ø min. 4.5 mm

132

14